

Schedule

NBR5590 / ASTM A106 / ASTM A53 / API 5L

Polegada	D. Externo (mm)	D. Interno (mm)	Parede (mm)	SCH	Kg/mt
1/4"	13,70	9,24	2,24	40	0,63
		7,68	3,02	80	0,80
3/8"	17,10	12,53	2,31	40	0,85
		10,75	3,20	80	1,10
1/2"	21,30	15,80	2,77	40	1,26
		13,88	3,73	80	1,62
		11,78	4,78	160	1,95
3/4"	26,70	20,93	2,87	40	1,68
		18,85	3,91	80	2,19
		15,55	5,56	160	2,89
1"	33,40	26,64	3,38	40	2,50
		24,30	4,55	80	3,23
		20,70	6,35	160	4,24
1.1/4	42,20	35,04	3,56	40	3,38
		32,46	4,85	80	4,46
		29,46	6,35	160	5,60
1.1/2"	48,30	40,90	3,68	40	4,05
		38,10	5,08	80	5,40
		33,98	7,14	160	7,25
2"	60,30	52,51	3,91	40	5,43
		49,25	5,54	80	7,47
		42,85	8,74	160	11,10
2.1/2"	73,00	62,71	5,16	40	8,62
		59,01	7,01	80	11,40
		53,97	9,53	160	14,90
3"	88,90	77,92	5,49	40	11,28
		73,66	7,62	80	15,25
		66,64	11,13	160	21,30
3.1/2"	101,60	90,12	5,74	40	13,56
		85,44	8,08	80	18,62
4"	114,30	102,26	6,02	40	16,06
		97,18	8,56	80	22,29
		92,04	11,13	120	28,25
		87,32	13,49	160	33,51
5"	141,30	128,30	6,55	40	21,76
		124,24	9,53	80	30,92
		115,90	12,70	120	40,24
		109,54	15,88	160	49,05
6"	168,30	154,06	7,11	40	28,23
		146,34	10,97	80	42,54
		139,74	14,27	120	54,20
		131,76	18,26	160	67,47

Polegada	D. Externo (mm)	D. Interno (mm)	Parede (mm)	SCH	Kg/mt
8"	219,10	206,38	6,35	20	33,28
		205,00	7,04	30	36,76
		202,72	8,18	40	42,49
		198,46	10,31	60	53,07
		193,68	12,70	80	64,57
		188,90	15,09	100	75,79
		182,56	18,26	120	90,32
		177,84	20,62	140	100,89
10"	273,00	174,62	22,23	XXS	107,78
		173,06	23,01	160	111,18
		260,35	6,35	20	41,73
		257,45	7,80	30	50,96
		254,51	9,27	40	60,24
		247,65	12,70	60	81,46
		242,87	15,09	80	95,84
		236,53	18,26	100	114,59
12"	323,80	230,17	21,44	120	132,85
		222,25	25,40	140	154,97
		215,93	28,56	160	172,11
		311,15	6,35	20	49,68
		307,09	8,38	30	65,14
		304,79	9,53	STD	73,76
14"	355,60	303,23	10,31	40	79,74
		298,45	12,70	XS	97,36
		295,31	14,27	60	108,97
		288,89	17,48	80	131,81
		280,97	21,44	100	159,67
		273,05	25,40	120	186,75
		266,69	28,58	140	207,87
		257,21	33,32	160	238,60
16"	421,90	342,90	6,35	10	54,63
		339,76	7,92	20	67,98
		336,54	9,53	30	81,21
		334,34	11,13	40	94,31
		330,20	12,70	XS	107,28
		325,42	15,09	60	126,51
		317,50	19,05	80	157,94
		307,94	23,83	100	194,64
18"	508,00	300,02	27,79	120	224,36
		292,10	31,75	140	253,32
		284,18	35,71	160	281,49

Schedule

NBR5590 / ASTM A106 / ASTM A53 / API 5L

Polegada	D. Externo (mm)	D. Interno (mm)	Parede (mm)	SCH	Kg/mt
16"	406,40	393,70	6,35	10	62,58
		390,56	7,92	20	77,92
		387,24	9,53	30	93,13
		381,00	12,70	40	123,18
		373,08	16,66	60	160,04
		363,52	21,44	80	203,26
		354,02	26,19	100	245,34
		344,48	30,96	120	286,33
		333,34	36,53	140	332,72
		325,42	40,49	160	364,94
18"	457,20	444,50	6,35	10	70,53
		441,36	7,92	20	87,85
		438,14	9,53	STD	105,05
		434,94	11,13	30	122,12
		431,80	12,70	XS	139,07
		428,66	14,27	40	155,90
		419,10	19,05	60	205,62
		409,54	23,83	80	254,24
		398,48	29,36	100	309,55
		387,34	34,93	120	363,33
		377,86	39,67	140	408,21
		366,72	45,24	160	459,18

Polegada	D. Externo (mm)	D. Interno (mm)	Parede (mm)	SCH	Kg/mt
20"	508,00	495,30	6,35	10	78,47
		488,95	9,53	20	116,97
		482,60	12,70	30	154,97
		477,82	15,09	40	183,14
		466,76	20,62	60	247,78
		455,62	26,19	80	310,91
		442,92	32,54	100	381,20
		431,80	38,10	120	441,06
22"	558,80	419,10	44,45	140	507,63
		407,98	50,01	160	564,24
		546,10	6,35	10	86,50
		539,74	9,53	20	129,01
		533,40	12,70	30	171,01
		527,04	15,88	40	212,52
		514,36	22,22	60	294,04
		501,66	28,57	80	374,04
24"	609,60	488,96	34,92	100	451,70
		476,26	41,27	120	527,37
		463,56	47,62	140	601,05
		450,86	43,97	160	672,73